## GROUND-WATER CONDITIONS IN UTAH, SPRING OF 1999

By

C.B. Burden, L.E. Spangler, and others
U.S. Geological Survey

Prepared by the U.S. Geological Survey
in cooperation with the Utah Department of Natural Resources,
Division of Water Resources and
Division of Water Rights

Published by the

Utah Department of Natural Resources

Division of Water Resources

Cooperative Investigations Report Number 40
1999

# **CONTENTS**

Introdu	ection
Utah's	ground-water reservoirs
Summa	ary of conditions
Major a	areas of ground-water development
(	Curlew Valley by J.D. Sory
(	Cache Valley by R.J. Eacret
]	East Shore area by T.A. Kenney
	Salt Lake Valley by K.K. Johnson
-	Гооеle Valley by B.L. Loving
1	Utah and Goshen Valleys by S.J. Brockner
J	Juab Valley by M.R. Danner
\$	Sevier Desert by Paul Downhour
	Central Sevier Valley by B.A. Slaugh
]	Pahvant Valley by R.L. Swenson
	Cedar Valley, Iron County by J.H. Howells
]	Parowan Valley by J.H. Howells
]	Escalante Valley
	Milford area by B.A. Slaugh
	Beryl-Enterprise area by H.K. Christiansen
	Central Virgin River area by H.K. Christiansen
(	Other areas by M.J. Fisher
1.	Map showing areas of ground-water development in Utah specifically referred to in this report
2.	Map of location of wells in Curlew Valley in which the water level was measured during March 1999
3.	Graphs showing relation of water level in selected wells in Curlew Valley to cumulative departure from average annual precipitation at Grouse Creek, to annual withdrawal from wells, and to concentration of dissolved solids in water from selected wells
4.	Map of location of wells in Cache Valley in which the water level was measured during  March 1999
5.	Graphs showing relation of water level in selected wells in Cache Valley to total annual discharge of the Logan River near Logan, to cumulative departure from average annual precipitation at Logan, Utah State University, to annual withdrawal from wells, and to concentration of dissolved solids in water from well (A-13-1)29bcd-1
6.	Map of location of wells in the East Shore area in which the water level was measured during March 1999
7.	Graphs showing relation of water level in selected wells in the East Shore area to cumulative departure from average annual precipitation at Ogden Pioneer Powerhouse, to annual withdrawal from wells, and to concentration of dissolved solids in water from well (B-4-2)27aba-1
8.	Map of location of wells in Salt Lake Valley in which the water level was measured during February 1999

#### **ILLUSTRATIONS—Continued**

9.	Graphs showing estimated population of Salt Lake County, total annual withdrawal from wells, annual withdrawal for public supply, and average annual precipitation at Salt Lake City Weather Service Office (International Airport)
10.	Graphs showing relation of water level in selected wells completed in the principal aquifer in Salt Lake Valley to cumulative departure from average annual precipitation at Silver Lake near Brighton, and relation of water level in well (D-1-1)7abd-6 to concentration of chloride and dissolved solids in water from the well
11.	Map of location of wells in Tooele Valley in which the water level was measured during March 1999
12.	Graphs showing relation of water level in selected wells in Tooele Valley to cumulative departure from average annual precipitation at Tooele and to annual withdrawal from wells
13.	Map of location of wells in Utah and Goshen Valleys in which the water level was measured during March 1999
14.	Graphs showing relation of water level in selected wells in Utah and Goshen Valleys to cumulative departure from average annual precipitation at Silver Lake near Brighton and Spanish Fork Powerhouse, to total annual withdrawal from wells, to annual withdrawal for public supply, to annual discharge of the Spanish Fork River at Castilla, and to concentration of dissolved solids in water from three wells
15.	Map of location of wells in Juab Valley in which the water level was measured during March 1999
16.	Graphs showing relation of water level in selected wells in Juab Valley to cumulative departure from average annual precipitation at Nephi, to annual withdrawal from wells, and to concentration of dissolved solids in water from well (D-13-1)7dbc-1
17.	Map of location of wells in part of the Sevier Desert in which the water level was measured during March 1999 in the shallow artesian aquifer
18.	Map of location of wells in part of the Sevier Desert in which the water level was measured during March 1999 in the deep artesian aquifer
19.	Graphs showing relation of water level in selected wells in the Sevier Desert to annual discharge of the Sevier River near Juab, to cumulative departure from average annual precipitation at Oak City, to annual withdrawal from wells, and to concentration of dissolved solids in water from well (C-15-4)18daa-1
20.	Map of location of wells in central Sevier Valley in which the water level was measured during March 1999
21.	Graphs showing relation of water level in selected wells in central Sevier Valley to annual discharge of the Sevier River at Hatch, to cumulative departure from average annual precipitation at Richfield, to annual withdrawal from wells, and to concentration of dissolved solids in water from well (C-23-2)15dcb-4
22.	Map of location of wells in Pahvant Valley in which the water level was measured during March 1999
23.	Graphs showing relation of water level in selected wells in Pahvant Valley to cumulative departure from average annual precipitation at Fillmore, to annual withdrawal from wells, and to concentration of dissolved solids in water from selected wells
24.	Map of location of wells in Cedar Valley, Iron County, in which the water level was measured during March 1999

#### **ILLUSTRATIONS—Continued**

25.	Graphs showing relation of water level in selected wells in Cedar Valley, Iron County, to cumulative departure from average annual precipitation at Cedar City Federal Aviation Administration Airport, to annual discharge of Coal Creek near Cedar City, to annual withdrawal from wells, and to concentration of dissolved solids in water from selected wells		
26.	Map of location of wells in Parowan Valley in which the water level was measured during March 1999		
27. Graphs showing relation of water level in selected wells in Parowan Valley to cumulati departure from average annual precipitation at Parowan Power Plant, to annual withdrafrom wells, and to concentration of dissolved solids in water from well (C-33-8)31ccc-			
28.	Map of location of wells in the Milford area in which the water level was measured during March 1999		
29.	Graphs showing relation of water level in selected wells in the Milford area to cumulative departure from average annual precipitation at Black Rock, to annual discharge of the Beaver River at Rocky Ford Dam, to annual withdrawal from wells, and to concentration of dissolved solids in water from well (C-28-11)25dcd-1		
30.	Map of location of wells in the Beryl-Enterprise area in which the water level was measured during March 1999		
31.	Graphs showing relation of water level in selected wells in the Beryl-Enterprise area to cumulative departure from average annual precipitation at Modena, to annual withdrawal from wells, and to concentration of dissolved solids in water from well (C-34-16)28dcc-2		
32.	Map of location of wells in the central Virgin River area in which the water level was measured during February 1999		
33.	Graphs showing relation of water level in selected wells in the central Virgin River area to annual discharge of the Virgin River at Virgin, to cumulative departure from average annual precipitation at St. George, to annual withdrawal from wells, and to concentration of dissolved solids in water from well (C-41-17)17cba-1		
34.	Map of location of wells in Cedar Valley, Utah County, in which the water level was measured during March 1999		
35.	Graphs showing relation of water level in selected wells in Cedar Valley, Utah County, to cumulative departure from average annual precipitation at Fairfield		
36.	Map of location of wells in Sanpete Valley in which the water level was measured during March 1999		
37.	Graphs showing relation of water level in selected wells in Sanpete Valley to cumulative departure from average annual precipitation at Manti		
38.	Graphs showing relation of water level in wells in selected areas of Utah to cumulative departure from average annual precipitation at sites in or near those areas		
TABLE	s		
1.	Areas of ground-water development in Utah specifically referred to in this report		
2.	Number of wells constructed and estimated withdrawal of water from wells in Utah		
3.	Total annual withdrawal of water from wells in significant areas of ground-water development in Utah, 1988-97		

#### **CONVERSION FACTORS**

Multiply	Ву	To obtain	
acre-foot	1,233	cubic meter	
foot	0.3048	meter	
gallon per minute	0.06308	liter per second	
inch	25.4	millimeter	
mile	1.609	kilometer	
square mile	2.590	square kilometer	

Chemical concentration is reported only in metric units—milligrams per liter. For concentrations less than 7,000 milligrams per liter, the numerical value is about the same as for concentrations in parts per million.

### **DEFINITION OF TERMS**

**Acre-foot**—The quantity of water required to cover 1 acre to a depth of 1 foot; equal to 43,560 cubic feet or about 326,000 gallons or 1,233 cubic meters.

**Aquifer**—A geologic formation, group of formations, or part of a formation that contains sufficient saturated permeable material to yield substantial amounts of water to wells and springs.

**Artesian**—Describes a well in which the water level stands above the top of the aquifer tapped by the well (confined). A flowing artesian well is one in which the water level is above the land surface.

**Dissolved**—Material in a representative water sample that passes through a 0.45–micron membrane filter. This is a convenient operational definition used by Federal agencies that collect water data. Determinations of "dissolved" constituents are made on subsamples of the filtrate.

**Land-surface datum (lsd)**—A datum plane that is approximately at land surface at each ground-water observation well.

Milligrams per liter—A unit for expressing the concentration of chemical constituents in solution. Milligrams per liter represents the mass of solute per unit volume (liter) of water.

Specific conductance—A measure of the ability of water to conduct an electrical current. It is expressed in microsiemens per centimeter at 25 degrees Celsius. Specific conductance is related to the type and concentration of ions in solution and can be used for approximating the dissolved-solids concentration of the water. Commonly, the concentration of dissolved solids (in milligrams per liter) is about 65 percent of the specific conductance (in microsiemens). This relation is not constant in water from one well or stream to another, and it may vary for the same source with changes in the composition of the water.

Cumulative departure from average annual precipitation—A graph of the departure or difference between the average annual precipitation and the value of precipitation for each year, plotted cumulatively. A cumulative plot is generated by adding the departure from average precipitation for the current year to the sum of departure values for all previous years in the period of record. A positive departure, or greater-than-average precipitation, for a year results in a graph segment trending upward; a negative departure results in a graph segment trending downward. A generally downward-trending graph for a period of years represents a period of generally less-than-average precipitation, which commonly causes and corresponds with declining water levels in wells. Likewise, a generally upward-trending graph for a period of years represents a period of greater-than-average precipitation, which commonly causes and corresponds with rising water levels in wells. However, increases or decreases in withdrawals of ground water from wells also affect water levels and can change or eliminate the correlation between water levels in wells and the graph of cumulative departure from average precipitation.

### WELL-NUMBERING SYSTEM

The well-numbering system used in Utah is based on the Bureau of Land Management's system of land subdivision. The well-numbering system is familiar to most water users in Utah, and the well number shows the location of the well by quadrant, township, range, section, and position within the section. Well numbers for most of the State are derived from the Salt Lake Base Line and the Salt Lake Meridian. Well numbers for wells located inside the area of the Uintah Base Line and Meridian are designated in the same manner as those based on the Salt Lake Base Line and Meridian, with the addition of the "U" preceding the parentheses. The numbering system is illustrated below.

